


FIELD NOTCH HEMS OF LOWER GABLE TRIM
 3" LONG AND 1/8" WIDE AT SPLICE. APPLY (2)
 3/8" BEADS OF NON-SKINNING BUTYL SEALANT
 TO TOPSIDE OF LOWER GABLE TRIM
 BEFORE ENGAGING



NOTE:
 FIELD CUT FIRST
 AND LAST PANELS
 TO EQUAL WIDTH.

1/8" POP RIVETS
 @ 12" O.C. THRU
 BUTYL SEALANT

3/16"x7/8"
 CONTINUOUS
 BUTYL TAPE

30# (NOT
 BY AEP-SPAN)

ANGLE TRIM

PANCAKE HEAD
 FASTENERS
 @ 12" O.C.

1/8" RIVETS
 AT TRIM LAP
 IN SEALANT LINE
 IF NECESSARY TO
 CLOSE "FISHMOUTH"

GABLE TRIM

CONTINUOUS
 PANEL CLEAT

PANCAKE FASTENER
 @ 12" O.C.


1/8" POP RIVETS @ 12" O.C. THRU
 RECEIVER TRIM AND ANGLE TRIM

RECEIVER TRIM

FIELD BEND PANEL
 UP 1"



CAP-SEAM



GABLE

CS3D8